

# Deployit JEE Plugin Manual

Version 3.7.0-IF

# Table of Content

CI Reference	3
Configuration Item Overview	3
Deployable Configuration Items	3
Virtual Deployable Configuration Items	3
Configuration Item Details	3
jee.DataSourceSpec	3
jee.Ear	3
jee.EjbJar	4
jee.JndiResourceSpec	4
jee.MailSessionSpec	5
jee.QueueConnectionFactorySpec	5
jee.QueueSpec	5
jee.ResourceSpec	6
jee.TopicConnectionFactorySpec	6
jee.TopicSpec	6
jee.War	6

# CI Reference

## Configuration Item Overview

### Deployable Configuration Items

CI	Description
<a href="#">jee.DataSourceSpec</a>	Deployable Java EE DataSource accessible via JNDI
<a href="#">jee.Ear</a>	Deployable EAR artifact
<a href="#">jee.EjbJar</a>	Deployable EJB JAR artifact
<a href="#">jee.MailSessionSpec</a>	Deployable Java EE Mail Session accessible via JNDI
<a href="#">jee.QueueConnectionFactorySpec</a>	Deployable Java EE JMS QueueConnectionFactory accessible via JNDI
<a href="#">jee.QueueSpec</a>	Deployable Java EE JMS Queue accessible via JNDI
<a href="#">jee.TopicConnectionFactorySpec</a>	Deployable Java EE JMS TopicConnectionFactory accessible via JNDI
<a href="#">jee.TopicSpec</a>	Deployable Java EE JMS Topic accessible via JNDI
<a href="#">jee.War</a>	Deployable WAR artifact

### Virtual Deployable Configuration Items

CI	Description
<a href="#">jee.JndiResourceSpec</a>	Deployable Java EE Resource accessible via JNDI
<a href="#">jee.ResourceSpec</a>	Description unavailable

## Configuration Item Details

### [jee.DataSourceSpec](#)

**Hierarchy** [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

**Interfaces** [udm.Taggable](#), [udm.Deployable](#), [udm.ConfigurationItem](#)

Deployable Java EE DataSource accessible via JNDI.

Public Properties
<b><a href="#">jndiName</a></b> : <a href="#">STRING</a> Name used to lookup this resource in JNDI
<b><a href="#">tags</a></b> : <a href="#">SET_OF_STRING</a> The tags to map deployables to containers.

### [jee.Ear](#)

**Hierarchy** [udm.BaseDeployableArchiveArtifact](#) >> [udm.BaseDeployableFileArtifact](#) >> [udm.BaseDeployableArtifact](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

**Interfaces** [udm.Taggable](#), [udm.Deployable](#), [udm.SourceArtifact](#), [udm.ArchiveArtifact](#), [udm.Artifact](#), [udm.DeployableArtifact](#), [udm.ConfigurationItem](#), [udm.FileArtifact](#)

Deployable EAR artifact.

**Public Properties****excludeFileNamesRegex** : *STRING*

Regular expression that matches file names that must be excluded from scanning

**placeholders** : *SET\_OF\_STRING*

Placeholders detected in this artifact

**scanPlaceholders** : *BOOLEAN* = *true*

Scan Placeholders

**tags** : *SET\_OF\_STRING*

The tags to map deployables to containers.

**Hidden Properties****textFileNamesRegex** : *STRING* = *.\+\. (cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt)*

Regular expression that matches file names of text files

**jee.EjbJar****Hierarchy** `udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem`**Interfaces** `udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact`

Deployable EJB JAR artifact.

**Public Properties****excludeFileNamesRegex** : *STRING*

Regular expression that matches file names that must be excluded from scanning

**placeholders** : *SET\_OF\_STRING*

Placeholders detected in this artifact

**scanPlaceholders** : *BOOLEAN* = *true*

Scan Placeholders

**tags** : *SET\_OF\_STRING*

The tags to map deployables to containers.

**Hidden Properties****textFileNamesRegex** : *STRING* = *.\+\. (cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt)*

Regular expression that matches file names of text files

**jee.JndiResourceSpec****Hierarchy** `jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem`**Interfaces** `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Deployable Java EE Resource accessible via JNDI.

#### Public Properties

**jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

## jee.MailSessionSpec

**Hierarchy** [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

**Interfaces** [udm.Taggable](#), [udm.Deployable](#), [udm.ConfigurationItem](#)

Deployable Java EE Mail Session accessible via JNDI.

#### Public Properties

**jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

## jee.QueueConnectionFactorySpec

**Hierarchy** [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

**Interfaces** [udm.Taggable](#), [udm.Deployable](#), [udm.ConfigurationItem](#)

Deployable Java EE JMS QueueConnectionFactory accessible via JNDI.

#### Public Properties

**jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

## jee.QueueSpec

**Hierarchy** [jee.JndiResourceSpec](#) >> [jee.ResourceSpec](#) >> [udm.BaseDeployable](#) >> [udm.BaseConfigurationItem](#)

**Interfaces** [udm.Taggable](#), [udm.Deployable](#), [udm.ConfigurationItem](#)

Deployable Java EE JMS Queue accessible via JNDI.

**Public Properties****jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

**jee.ResourceSpec****Hierarchy** `udm.BaseDeployable >> udm.BaseConfigurationItem`**Interfaces** `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Description unavailable

**Public Properties****tags** : `SET_OF_STRING`

The tags to map deployables to containers.

**jee.TopicConnectionFactorySpec****Hierarchy** `jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem`**Interfaces** `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Deployable Java EE JMS TopicConnectionFactory accessible via JNDI.

**Public Properties****jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

**jee.TopicSpec****Hierarchy** `jee.JndiResourceSpec >> jee.ResourceSpec >> udm.BaseDeployable >> udm.BaseConfigurationItem`**Interfaces** `udm.Taggable, udm.Deployable, udm.ConfigurationItem`

Deployable Java EE JMS Topic accessible via JNDI.

**Public Properties****jndiName** : `STRING`

Name used to lookup this resource in JNDI

**tags** : `SET_OF_STRING`

The tags to map deployables to containers.

**jee.War**

**Hierarchy** udm.BaseDeployableArchiveArtifact >> udm.BaseDeployableFileArtifact >> udm.BaseDeployableArtifact >> udm.BaseDeployable >> udm.BaseConfigurationItem

**Interfaces** udm.Taggable, udm.Deployable, udm.SourceArtifact, udm.ArchiveArtifact, udm.Artifact, udm.DeployableArtifact, udm.ConfigurationItem, udm.FileArtifact

Deployable WAR artifact.

### Public Properties

**excludeFileNamesRegex** : **STRING**

Regular expression that matches file names that must be excluded from scanning

**placeholders** : **SET\_OF\_STRING**

Placeholders detected in this artifact

**scanPlaceholders** : **BOOLEAN** = *true*

Scan Placeholders

**tags** : **SET\_OF\_STRING**

The tags to map deployables to containers.

### Hidden Properties

**textFileNamesRegex** : **STRING** = *.\+\. (cfg | conf | config | ini | properties | props | txt | asp | aspx | htm | html | jsf | jsp | xht | xhtml | sql | xml | xsd | xsl | xslt)*

Regular expression that matches file names of text files